

# LoRa® SPY TO



 $\label{thm:lem:temperature} Temperature\ recorder$  with a long-range LoRaWAN  $^{\text{TM}}$  connectivity



## **Presentation**

The LoRa® SPY T0 recorder measures and records temperature.

Data are sent to the JRI secure Cloud by the LoRaWAN<sup>TM</sup> network of the telecom operators members of the LoRa Alliance<sup>TM</sup>, or by a local network. In case of thresholds excursion, real-time alerts are sent.

Robust and waterproof, it is adapted to the cold chain monitoring during transportation.

## **Technical features**

Communication frequency	868 MHz	915 MHz
Interface	Status LED lights, On/Off touch sensitive button	
Measurement range	-35°C to +85°C	
Accuracy	$\pm 0.5^{\circ}\text{C}$ from -20°C to +30°C and $\pm 0.8^{\circ}\text{C}$ out of this range	
Memory	10 000 data points	
Radio range	Up to 16 km open field range	
Sensor	Internal Class A PT 100	
Resolution	0.01	
Measuring interval	Adjustable from 1 mn to 5 mn	
Transmission & recording interval (internal memory)	Adjustable from 1 mn to 24 hrs	
Response time $\sigma_{90}$	~15 mn	
Operating conditions	-35°C to +85°C	
Protection	IP68	
Case	Polycarbonate – Food contact	
Dimensions and weight	87 x 64 x 25 mm / ~ 100 g	
Power supply	Replaceable Lithium 3,6v battery	
Battery lifetime	2 years	
Fixation	Fixing eyelets	
Supplied with	Battery, user manual on www.jri-corp.com	
Compliance	CE, ROHS, FCC, EN 300-320, NF EN 12830	
Standard calibration points	-18°C/+5°C/+25°C	

#### **Benefits**

Easy-to-use
 The recorder is ready-to-use and has operating and alarm lights



- Excellent measurement accuracy
- Several modes of data exploitation



#### PART NRS

11801 EX: LoRa® SPY TO 868 MHz (without battery) 12266 EX: LoRa® SPY TO 915 MHz (without battery) 17 347b EN 01 06